

MAC PLANTMASTER ELECTRIC S.S.

Electrically Heated Static Pressure Washer

- 80°C with market leading heat retention
- 375lt stainless steel lagged water tank
- Premium quality 316L stainless steel cabinet
- Larger water tank and increased heating power gives a longer run time with constant heat



KEY SPECIFICATION

80°C Maximum Heat

11lt-18lt/min Water Flow

18kw-48kw Heating Power

120-200bar Pressure

400v, 32amp Minimum
Power Supply



MAC PLANTMASTER ELECTRIC S.S.



THREE REASONS TO CHOOSE STAINLESS STEEL

- Our 316L stainless steel cabinets are the pinnacle of quality and durability
- Guaranteed rust-proof to suit all environments
- A great looking cabinet for the long term

STANDARD FEATURES

- Low revving 1450rpm pump & motor
- High temperature Interpump
- Unique stainless steel subframe construction
- Easy access for servicing
- Double insulated hot water tank
- Low thermal loss in standby
- Maximum temperature output 80°C
- Digital temperature display
- Simple 24v controls
- Available from 18-48kw heating power
- Lockable powder coated steel front door
- Hinged and removable cabinet front door and lid

CABINET FINISH

- Full 316L stainless steel cabinet with lockable controls

OPTIONAL ACCESSORIES AVAILABLE



THE MAC 18/24 MACHINE DESIGNED TO RUN ON A STANDARD 32AMP POWER SUPPLY - INNOVATION IN TECHNOLOGY

	PLANTMASTER SSE1	PLANTMASTER SSE2	PLANTMASTER SSE3	PLANTMASTER SSE4	PLANTMASTER SSE5	PLANTMASTER SSE6	PLANTMASTER SSE7
Water Flow	11lt per minute	13lt per minute	13lt per minute	15lt per minute	13lt per minute	15lt per minute	18lt per minute
Pressure	120bar	170bar	170bar	200bar	170bar	200bar	160bar
Motor Specification	3kW, 4hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm	5.5kW, 7.5hp, 1450rpm
Heating Power	18-24kW	24Kw	36Kw	36Kw	48Kw	48Kw	48Kw
Volts Amps Watts	400v/32A/22Kw	400v/45A/29.5Kw	400v/63A/41.5Kw	400v/63A/41.5Kw	400v/80A/41.5Kw	400v/80A/41.5Kw	400v/80A/41.5Kw
Shutdown System	Timed total stop	Timed total stop	Timed total stop	Timed total stop	Timed total stop	Timed total stop	Timed total stop
Max. Temperature	80°C	80°C	80°C	80°C	80°C	80°C	80°C
Weight	250kg	250kg	250kg	250kg	250kg	250kg	250kg
Dimensions (h x w x d)	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm	130 x 100 x 180cm